

NeuCo, Inc.

- Integrated Optimization Software on three 600 MW units reduces emissions, increases efficiency, and increases reliability.
- Five Optimization Modules: cyclone combustion, sootblowing, SCR operations, thermal performance, and profit optimization.
- Higher efficiencies help to meet Climate Change goals.
- Total Project funding: \$19.1 million (DOE share: \$8.5 million).





Dynegy Midwest Generation's Baldwin Energy Complex



A CCPI Round 1 Project

Background

 NeuCo, Inc. will demonstrate integration of existing controls, control systems, sensors, and computer hardware with advanced optimization techniques on three coal-fired units totaling 1765 MWe.

 Units 1 and 2 consist of cyclone-fired (2x585 MWe) boilers with SCR systems, and Unit 3 consists of a tangentially-fired

(595 MWe) boiler with LNBs.

Project Location:
 Dynegy Midwest Generation's
 Baldwin Energy Complex,
 Baldwin, IL.






Background

 Integrated Optimization Software is becoming an important tool supporting control and management objectives as plant complexity increases through retrofits, repowering, modifications, and new technologies.

 This project builds on NeuCo's ProcessLink[™] technology platform that includes neural networks, genetic algorithms,

and fuzzy logic techniques.





Technology Uniqueness

- Overall architecture of control platform permits flexible deployment strategies. Application architecture built around interoperable services.
- Service module allows applications to leverage networked computational resources rather than requiring all data and logic to be resident on a single computer.
- Optimization techniques can be applied to a variety of systems within coal power plants using existing control technologies, linking these systems together.
- Increasing complexity of modern power plants will require an integrate process optimization approach.

Schedule

- NEPA Process
 - Categorical Exclusion Completed
- Combustion Optimization
 - Start 02/04 Finish 02/08
- Soot Optimization
 - Start 02/04 Finish 02/08
- SCR Optimization
 - Start 02/04 Finish 02/08
- Performance Optimization
 - Start 02/04 Finish 02/08
- Profit Optimization
 - Start 02/04 Finish 02/08



Potential Benefits

Application of this technology will result in:

- Increased thermal efficiency by ~1.5%.
- One year extension of SCR catalyst and 15% reduction of NH₃ consumption.
- NOx emissions reductions of 5%.
- Reductions in emissions of CO₂, mercury, and particulates (due to increased thermal efficiency).
- Lower costs to consumers and an increase in power company profitability due to overall plant reliability and efficiency.



Potential Benefits

- Successful commercial application of Integrated Optimization Software System in the U.S. would significantly reduce NOx emissions:
 - 13,420 tpy of NOx with cyclone optimization
 - 64,990 tpy of NOx with sootblowing optimization
- By installing optimization technologies, power companies could save annually:
 - \$ 7.5 million for SCR units
 - \$28.6 million for sootblowing operations
 - \$51.5 million for performance improvement
 - \$51.5 million for profit optimization



Benefits Analysis www.NETL.DOE.GOV/coalpower/CCPI/Index.html